



Galvanized steel flexible conduit is suitable for concealed, exposed or approved raceways. The flexible conduit is manufactured with a continuous spiral wound strip of corrosion rust resistant, hot dipped galvanized steel.

Its Benefits:

- Smooth interior for easy wire pulling
- Able to withstand high temperatures
- Durable crush-proof construction
- Corrosion and rust resistant

The natural color type RWS conduit features a smooth metal interior for easy wire pulling. The flexible steel conduit is wire temperature rated, and has superior crush proof qualities.

Applications:

- Motor Feeder, Branch, Control circuit conductors and cable
- Environmental air-handling spaces.
- Concealed or exposed installations
- Elevators, hoistways escalators

FLEXIBLE METAL CONDUIT—STEEL (WEIGHTS AND DIMENSIONS)

Code	Trade Size	Internal Diameter mm.		Outside Diameter mm.		Min. Bending Radius (mm)	Length of Conduit (M/Roll)
		Min.	Max.	Min.	Max.		
C-FC0050	½"	15.8	16.2	19.5	19.9	65	30
C-FC0075	¾"	20.8	21.3	24.7	25.2	75	30
C-FC0100	1"	26.4	27.1	31.6	32.1	100	15
C-FC0125	1 ¼"	35.0	35.5	40.0	40.5	125	15
C-FC0150	1 ½"	40.1	40.6	45.8	46.3	150	10
C-FC0200	2"	50.5	51.2	57.3	58.0	175	7.5

Other Sizes are also available upon request